# Characterization and 3-D Modeling of Devonian Pinnacle Reefs for CO<sub>2</sub> Storage and Enhanced Oil Recovery

2014 Rocky Mountain Section AAPG Annual Meeting
Denver, Colorado
July 20–22, 2014


J.R. Braunberger, N.W. Bosshart, R.C.L. Klenner, G. Liu, W.D. Peck, C.D. Gorecki





### **Presentation Outline**

- Introduction
  - Plains CO<sub>2</sub>
     Reduction (PCOR)
     Partnership
  - Devonian PinnacleReef Overview
- 3-D Modeling
- Dynamic Simulation
- Results and Discussion
- Conclusion







## **PCOR Partnership**

**PCOR Partnership** 2003 - Present



























































































































































































































# Introduction






(Modified from Jin and Bergman, 2001)

(Modified from Core Laboratories' Stratigraphic Correlation Chart: www.landman.ca/pdf/CORELAB.pdf)







### Devonian Reef Overview: Keg River Formation



#### Zama Sub-basin Keg River Pinnacle Reefs


- Up to 400 ft in relief
- 40 acres (0.16 km²) at base
- Largely dolomitic
- Intergrain to microfracture porosity
- Encased in Muskeg anhydrite






# CO<sub>2</sub> EOR Case Study: Zama Oil Field, Northwestern Alberta


- PCOR Partnership Demonstration in cooperation with Apache Canada
- Acid gas (70% CO<sub>2</sub> + 30% H<sub>2</sub>S) injection since December 2006
  - CO<sub>2</sub> EOR, CO<sub>2</sub> storage, and H<sub>2</sub>S disposal
- Results through May 2012:
  - 121,200 metric tons of injected acid gas
  - 74,000 barrels of oil produced
  - Storage of approximately 36,600 metric tons of CO<sub>2</sub>









### **Devonian Reef Overview: Winnipegosis Formation**








#### Williston Basin Winnipegosis Pinnacle Reefs

- Up to 350 ft in relief
- 0.3 to 3 miles base diameter
- Largely dolomitic
- Intergrain to vuggy porosity
- Encased in Prairie evaporites







# **Modeling Workflow**




# Structural Surface and Grid Development



# Winnipegosis: MPS Facies Modeling



# Petrophysical Property Modeling with Conditioning to Facies




# Static Storage Potential of Various Sized Reefs

#### Static Storage Potential (assuming total formation fluid displacement):

| Model Size | Net Volume (ft³) | Pore Volume (ft³) | CO <sub>2</sub><br>Density<br>(lb/ft³) | Static Storage Potential (tons CO <sub>2</sub> ) |
|------------|------------------|-------------------|--|--|
| 0.3 Mile   | 392,902,594      | 42,054,576        | 38.15                                  | 802,191  |
|            |                  |                   |  |  |
| 1.5 Mile   | 16,226,536,038   | 1,617,963,868     | 38.15                                  | 30,862,661                                       |
|            |                  |                   |  |  |
| 3 Mile     | 68,358,862,682   | 6,802,061,062     | 38.15                                  | 129,749,315                                      |

# Oil Saturation Modeling



## CO, EOR Recoverable Oil Estimates


(Calculated from core residual oil saturations; OIP is likely underestimated.)


| 0.3-mile Pinnacle Reef |                     |              |                 |                             |  |  |
|------------------------|---------------------|--------------|-----------------|-----------------------------|--|--|
| HCPV (RB)              | Shrinkage<br>Factor | STOIIP (STB) | Recovery Factor | Total Recoverable Oil (STB) |  |  |
| 54,573                 | 1.2                 | 45,478       | 5%              | 2274                        |  |  |
| 54,573                 | 1.2                 | 45,478       | 10%             | 4548                        |  |  |
| 54,573                 | 1.2                 | 45,478       | 15%             | 6822                        |  |  |
| 1.5-mile Pinnacle Reef |                     |              |                 |                             |  |  |
| HCPV (RB)              | Shrinkage<br>Factor | STOIIP (STB) | Recovery Factor | Total Recoverable Oil (STB) |  |  |
| 2,692,104              | 1.2                 | 2,243,420    | 5%              | 112,171                     |  |  |
| 2,692,104              | 1.2                 | 2,243,420    | 10%             | 224,342                     |  |  |
| 2,692,104              | 1.2                 | 2,243,420    | 15%             | 336,513                     |  |  |
| 3-mile Pinnacle Reef   |                     |              |                 |                             |  |  |
| HCPV (RB)              | Shrinkage<br>Factor | STOIIP (STB) | Recovery Factor | Total Recoverable Oil (STB) |  |  |
| 10,824,245             | 1.2                 | 9,020,204    | 5%              | 451,010                     |  |  |
| 10,824,245             | 1.2                 | 9,020,204    | 10%             | 902,020                     |  |  |
| 10,824,245             | 1.2                 | 9,020,204    | 15%             | 1,353,031                   |  |  |

<sup>\*\*\*</sup> These numbers are representative of hypothetical, average Winnipegosis pinnacle reefs differing on the basis of size.

# Dynamic Simulation for CO<sub>2</sub> Injectivity Analysis

- Multiple cases were run considering different optimization parameters to achieve maximum injectivity.
  - Number of wells (injectors vs. producers)
  - Vertical vs. horizontal
  - Duration of injection





# Dynamic Simulation for CO<sub>2</sub> Injectivity Analysis

- Preliminary results (selected):
  - 0.3-mile simulations: 5 years
  - 1.5-mile simulations: 10 years
  - 3-mile simulations: 20 years (except Case 5)
- More than 3 million tons of simulated injectivity in the 3-mile reef model with four operating wells over a span of 30 years, but...
  - Some economic considerations: drilling wells costs money, horizontal wells are more expensive than vertical wells, injecting over a longer time costs more money.
  - Injection efficiency: the most injected CO<sub>2</sub> with the fewest wells in the shortest amount of time.

| Model Size | Case   | Well<br>Configuration                               | Total CO <sub>2</sub><br>Injected,<br>(ton) | Efficiency (Total<br>Injected CO <sub>2</sub> /Static<br>Storage Potential), % |
|------------|--------|---|---|--|
| 0.3 mile   | Case 1 | one injector + one producer                         | 44,171                                      | 5.51   |
| 0.3 mile   | Case 2 | one injector + one producer horizontal perforation  | 57,357                                      | 7.15   |
|            |        |   |   |  |
| 1.5 mile   | Case 1 | one injector + one producer                         | 521,590                                     | 1.69   |
| 1.5 mile   | Case 2 | one injector + one producer horizontal perforation  | 726,461                                     | 2.35   |
| 1.5 mile   | Case 3 | one injector + two producers horizontal perforation | 793,798                                     | 2.57   |
| 1.5 mile   | Case 4 | two injectors + two producers                       | 875,415                                     | 2.84   |
|            |        |   |   |  |
| 3 mile     | Case 1 | one injector  | 340,682                                     | 0.26   |
| 3 mile     | Case 2 | one injector + one producer                         | 1,030,370                                   | 0.79   |
| 3 mile     | Case 3 | one injector + one producer horizontal perforation  | 1,516,140                                   | 1.17   |
| 3 mile     | Case 4 | one injector + two producers                        | 1,924,970                                   | 1.48   |
|            |        | horizontal perforation                              |   |  |
| 3 mile     | Case 5 | two inj. + two<br>prod., 30 yr                      | 3,212,800                                   | 2.48   |

## **Discussion and Conclusion**

- Geocellular modeling objectives:
  - Characterizing the pinnacle reef structures
  - Replicating the natural heterogeneity thought to be present in the reservoir
  - Increasing our knowledge of reef potential in the applications of CO<sub>2</sub> EOR and storage
- Modeled reefs are a product of averages
  - Variability is noted in pinnacle reef population





## **Discussion and Conclusion**

- The 0.3-mile-diameter model shows limited feasibility for production or injection.
- Simulation cases with only one injector exhibit minimal injectivity.
- The 1.5-mile- and 3-mile-diameter model analyses show more promising results
  - CO<sub>2</sub> EOR recoverable reserves greater than 500,000 bbl possible
  - Potential geologic storage in excess of 1 million tons of CO<sub>2</sub>.





## **Discussion and Conclusion**

- Geologic storage of CO<sub>2</sub> is becoming a more popular idea.
  - Zama Field case study (NW Alberta) showing promising results.
  - "With over 700 pinnacle reef structures in the Zama subbasin, a careful selection of eight to sixteen pinnacle structures can provide a total storage capacity in excess of 10 MMt over the project span ranging from 4.5 years to 20 years" (Saini and others, 2013).
- Geologic CO<sub>2</sub> storage will be utilized more in the future and may prove to be an important tool for a "greener" and more sustainable existence.







# Thank you.





### **Contact Information**

# Energy & Environmental Research Center

University of North Dakota 15 North 23rd Street, Stop 9018 Grand Forks, ND 58202-9018

World Wide Web: **www.undeerc.org** Telephone No. (701) 777-5334 Fax No. (701) 777-5181

Nick Bosshart, Research Scientist nbosshart@undeerc.org





# References

- Burke L. PCOR project Apache Zama F Pool acid gas EOR & CO2 storage. Report prepared by RPS Energy Canada for the Energy & Environmental Research Center, 2009.
- Ehrets, J.R., and Kissling, D.L., 1987, Winnipegosis platform margin and pinnacle reef reservoirs, northwestern North Dakota, in Fischer, D.W., ed., Fifth International Williston Basin Symposium: North Dakota Geological Survey, Grand Forks, North Dakota, p. 131.
- Jin, J., Bergman, K.M., 2001. Revised Stratigraphy of the Middle Devonian (Givetian)
   Winnipegosis Carbonate-Prairie Evaporite Transition, Elk Point Group, Southern
   Saskatchewan. Bulletin of Canadian Petroleum Geology, Vol.49, No.4, P.441457.
- Saini, D, Gorecki, C.D., Knudsen, D.J, Sorensen, J.A., Steadman, E.N., 2013, A simulation study of simultaneous acid gas EOR and CO<sub>2</sub> storage at Apache's Zama F Pool: Elsevier, Energy Procedia, v.37, p. 3891–3900.
- Smith, S.A., Sorensen, J.A., Steadman, E.N., Harju, J.A., Jackson, B., Nimchuk, D., Burke, L., 2010. Plains CO<sub>2</sub> Reduction (PCOR) Partnership (Phase II) –Zama Field Validation Test Regional Technology Implementation Plan, U.S. Department of Energy, National Energy Technology Laboratory, Morgantown, West Virginia.





### **Acknowledgment**

This material is based upon work supported by the U.S. Department of Energy National Energy Technology Laboratory under Award Nos. DE-FE0009114 and DE-FC26-05NT42592.

#### **Disclaimer**

This presentation was prepared as an account of work sponsored by an agency of the United States Government. Neither the United States Government, nor any agency thereof, nor any of their employees, makes any warranty, express or implied, or assumes any legal liability or responsibility for the accuracy, completeness, or usefulness of any information, apparatus, product, or process disclosed or represents that its use would not infringe privately owned rights. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof. The views and opinions of authors expressed herein do not necessarily state or reflect those of the United States Government or any agency thereof.



